

# CREE Stellar



Guide artikelkod ljusfiler Cree Lighting STELLAR Hi-Bay

ex  
STL-A-NM-12-31L-308

STL - Produktserie STELLAR

A - Version

NM - Standard fäste EyeBolt

STL-HK-13L Upphångningskrok i rostfritt modell "S"+"M" 13L/20L (option)

STL-HK-27L Upphångningskrok i rostfritt modell "L"+"XL" 27L/31L (option)

UB Universalfäste (montagebygel) för tex vägg eller takmontage

Spridning 12=120 grader 60=60 grader 90=90 grader

Ljusflöde (lm) 13L=13000lm (S), 20L=20000lm (M), 27L=27000lm (L), 31L=31000lm

(XL)

CCT 308=3000K CRI>=80, 408=4000K CRI>=80, 508=5000K CRI>=80

## Ordering Information

EX: STL-A-NM-60-13L-408-+-24-45-WH-DIM +STL-HK-13L

STL	A	NM	60	13L	408	+	24	45	WH	DIM
Product	Version	Mounting	Optic	Lumen Package	CCT	Insulation Class	Voltage	Operation Temperature	Finish	Control Option
STL Stellar High Bay	A	NM Eyebolt	60 60°	13L SMALL	308* 30K 80CRI	+	24 220-240V	45 -35° - +45°	WH White	DIM** 1-10V
			90 90°	20L MEDIUM	408 40K 80CRI					DL DALI
			12 120°	27L LARGE	508 50K 80CRI					
				31L EXTRA-LARGE						

\* On request with MQD Ordering information is for reference only. Some product configurations are not available. Please consult spec sheets for specific product availability and for further details.  
\*\*Available also with presence sensor.

